



DEVBULK CANSEN

Technical Specifications

Built / Ship Yard	2014 / Minaminippon
Flag	Marshall Islands
Class	Rina & P&I Uk Club & ITF
P&I Club	UK Club
Type	Bulk Carrier / Open Hatch Super Box
Dwt	36706 mts on 10.41 m Summer
Tpc	46,5 mt on Summer Draft
L.o.a	177.00 m
Beam	29,50 m
Light Ship	7,859 mts
Moulded Depth	14,50 m
Tonnage Gt / Nt	22,160 /11,757



	Summer	Winter	Tropical
Deadweight	36.706,7	35.692,0	37.723,6
Draft	10,415	10,198	10,632
Freeboard	4,138	4,355	3,921

Hatch Cover No	1	2	3	4	5
Hatch Cover Size	15,20 x 17,0 m	20,00 x 25,00 m	20,00 x 25,00 m	20,00 x 25,00 m	20,00 x 25,00 m
Tank Top dimensions (Fwd X Aftx X Length)	7,20 x 17,0 x 24,6 m	25,0 x 25,0 x 27,2 m	25,0 x 25,0 x 25,4 m	25,0 x 25,0 x 25,6 m	25,0 x 10,8 x 27,0 m
Hold Capacity	1	2	3	4	5
Grain / Bale (Cub.m)	5.734,30 / 5618,10	9.928,70 / 9,665,50	9.301,20 / 9.115,50	9.343,80 / 9.156,80	9.421,70 /9.238,00

Total

Type of Hatch Cover	Hydraulic Folding Type
Gear	4 Cranes x 30 mts SWL
Grab	N/ A
Ventilation/A60/CO2/ITF	Elec / Yes / Yes / Yes
Tanktop Strength	21,0 mts / sqm
Hatch Cover Strength	No : 1 2,0 mts / sqm & No 2 : ,3,4,5 : 1,75 mts/sqm
Main Engine	Man - B&W 6S50MC // 6780 kw
Generators:	Yanmar x 3 Set
Bunker Capacity %85	Hs - Ls lfo : 1.300 m3 & Mgo : 280 m3

Speed / Consumption

Laden Condition	Abt 12,00 knots abt 16,50 mt VLSIFO/HSFO + 0,1mt LSMGO/HSFO
Ballast Condition	Abt 12,50 knots abt 16,50 mt VLSIFO/HSFO + 0,1mt LSMGO/HSFO
Port Consumption	Abt 3,0 mt/day VLSIFO
Winches Working	Abt 5,6 mt/day VLSIFO



devbulk.com

ALL ABT, TAKEN PLAN BUT WITHOUT GUARANTEE